
GP Batteries

Product Specification



Product Name GP MP10MA Portable PowerBank with Type C port Description Back up power for USB powered electronic devices

(e.g. smartphones, tablet PCs)

Battery Rating Lithium Polymer 3.7V 10000mAh 37Wh

Micro USB Port Input 2A / 5V DC

Output 2.4A / 5V DC USB Port (x2)

USB Type C Input 3A / 5V DC; Output: 3A / 5V DC

Total 3A for 3 output ports

Application Charge USB powered electronic devices

Recharging Time 4.5 hours by 5V/3A at USB-C port;


Discharging Time 2 hours at 3A via USB-C port

(The discharging time may vary for different devices)

Operation Temperature : 5°C to 40°C

Safety protection 1) Over current protection

2) 1st Level over charging & discharging protection



Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

GP Batteries

Product Specification

3) 2nd Level over charging & discharging protection

Model no.: MP10MA

- 4) Short circuit protection
- 5) Over temperature protection
- 6) Under temperature protection
- 7) Loop back protection

LED Indication : Charging & Discharging the Portable PowerBank

Table 1

Charging & Discharging Condition	LED Indicator
Charging	Last LED flashing
Discharging	Refer to battery status (Table 2)
Fully charged	All LEDs On
Errors	1 st LED Fast flashing & then off

Press button to show battery status:

Table 2


Battery Strength	LED indicator
Good	Four LED on
Good to average	First Three LED on
Average	First Two LED on
Weak	One LED on
No Power	No LED

Dimension : 135.5 (L) x 70 (W) x 13.5 (H) mm (+/- 0.5mm)

Weight : 233g (approx.)

Certification : CE, FCC, UN38.3, IEC62133 (Pending), IEC60950 (Pending)

Warranty Period : 12 months from ex-factory date



Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.